

## SPECIFICATION

Specification		BB-800	BB-900	BB-1000
Power rating		AC 220-240V 50 ~ 60 Hz 660W		
Water Inlet Type	Type	Direct Inlet Flow Type		
	Water Inlet Pressure	0.4 ~ 7.5 kgf/cm <sup>2</sup> (5.69 psi ~ 106.7 psi)		
Power cord		grey 1.2 metres	white 1.8 metres	
Wash Function	Posterior Wash	Maximum 1.2 litres / min		
	Feminine wash	Maximum 1.2 litres / min		
	Water Pressure Adjustable	5 steps		
	Warm Water Temperature	4 steps Room Temp ~ 40°C		
	Heater	600W		
	Safety Devices	Thermal Fuse, Thermal Switch, Float Switch		
Heated Seat	Temperature	4 steps Room Temp ~ 42°C		
	Heater	55W		
	Safety Devices	Thermal fuse		
Warm Air Drier Device	Adjustable Dry Temperature	4 steps Room Temp ~ 45°C		
	Heater	250W		
	Safety Devices	Thermal fuse (bimetal)		
Enema Function		Yes	Yes	Yes
Deodoriser		No	Yes	Yes
Remote Control		No	Yes	Yes
Inlet Water Temperature		3 ~ 35°C (37.4°F ~ 95°F)		
Ambient Temperature		3 ~ 40°C (37.4°F ~ 104°F)		
Overall Dimensions	Round Shape	W: 495mm X L: 500mm X H:185mm	W: 495mm X L: 500mm X H:185mm	W: 475mm X L: 500mm X H:185mm
	Elongated Shape	W: 495mm X L: 525mm X H:185mm	W: 495mm X L: 525mm X H:185mm	W: 475mm X L: 525mm X H:185mm
Weight		5.3kg (11.6 lbs)	5.3kg (11.6 lbs)	5.4kg (11.9 lbs)
Shipping Dimensions		W: 535mm X L: 575mm X H:240mm	W: 535mm X L: 575mm X H:240mm	W: 535mm X L: 575mm X H:240mm
Shipping Weight		8.2kg	8.2kg	8.4kg